

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

## AMENDMENTS TO THE CLAIMS

1. (currently amended) A system for exchanging heat with a fluid, for heating the fluid, comprising:

a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, comprising a heating element, for heating the fluid, a channel, for enabling the fluid to flow thereinto and therefrom, and for enabling the fluid to be stored therein adapted to heat the heat exchanger, and a storing element, for enabling the storing of fluid in the channel, the heating of the fluid stored in the channel to a stored heated fluid temperature, and the maintaining of the fluid in the channel at the stored heated fluid temperature, and for enabling the fluid to be substantially rapidly heated by the heating element to a fluid dispensing temperature above the stored heated fluid temperature for dispensing of the fluid adapted to be heated by the heating element, and further adapted to maintain the fluid at a heated fluid temperature, and to enable the fluid to be heated above the heated fluid temperature substantially rapidly to a fluid dispensing temperature;

~~a fluid inlet, for enabling the fluid to flow into the heat exchanger; and~~

~~a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger.~~

2. (cancelled)

3. (original) The system of claim 1, wherein the heat exchanger is comprised of aluminum.

4. (original) The system of claim 1, further comprising a sealing element for sealing the heat exchanger.

5. (currently amended) The system of claim 1, ~~wherein the~~ further comprising a fluid inlet comprises an inlet valve.

6. (currently amended) The system of claim 1, ~~wherein the~~ further comprising a fluid outlet comprises an outlet valve.

7. (original) The system of claim 1, further comprising a sensing element for sensing the temperature of the heat exchanger, and for controlling and stabilizing the temperature thereof.

8. (original) The system of claim 1, further comprising a system for dispensing the fluid, which includes the heat exchanger therein.

9. (currently amended) The system of claim 1, further comprising a fluid inlet, for enabling the fluid to flow into the channel, and a fluid outlet, for enabling the fluid to flow out of the channel, and wherein the storing element is further adapted to retain heat, such that, upon turning off the heating element and the fluid inlet after dispensing fluid, any fluid remaining in the channel ~~heat exchanger~~ evaporates through the fluid outlet responsive thereto.

10. (original) The system of claim 1, further comprising a flow-controlling element for controlling the flow of the fluid from the fluid outlet for dispensing thereof.

11. (original) The system of claim 1, further comprising an operation-controlling element for controlling the operation of the system.

12. (currently amended) The system of claim 1 ~~2~~, wherein the storing element is adapted to enable the fluid to be in direct contact therewith.

13. (cancelled)

14. (currently amended) The system of claim 1 ~~2~~, wherein the heating element is generally m-shaped.

15. (currently amended) The system of claim 1 ~~2~~, wherein the heating element is adapted to be connected to a heating source.

16. (currently amended) The system of claim 1 ~~2~~, wherein the channel is in the shape of a spiral ~~generally spiral-shaped~~.

17. (original) The system of claim 8, wherein the heat exchanger is located generally in the upper portion of the fluid dispensing system.

18. (original) The system of claim 8, wherein the fluid dispensing system further includes an outlet for dispensing the heated fluid.

19. (original) The system of claim 10, wherein the flow-controlling element comprises a flowmeter.

20. (original) The system of claim 11, wherein the operation-controlling element comprises a processing element for processing the temperature of the heat exchanger.

21. (original) The system of claim 18, wherein the fluid dispensing outlet comprises a fluid spray head.

22. (original) The system of claim 20, wherein the processing element comprises a microprocessor.

23. (currently amended) A system for exchanging heat with a fluid, for heating the fluid, comprising:

heat exchanging means a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, comprising heating means, for heating the fluid, a channel, for enabling the fluid to flow thereinto and therefrom, and for enabling the fluid to be stored therein, and storing means, for enabling the storing of fluid in the channel, the heating of the fluid stored in the channel to a stored heated fluid temperature, and the maintaining of the fluid in the channel at the stored heated fluid temperature, and for enabling the fluid to be substantially rapidly heated by the heating means to a fluid dispensing temperature above the stored heated fluid temperature for dispensing of the fluid adapted to store heat

~~energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein;~~

~~a fluid inlet, for enabling the fluid to flow into the heat exchanger; and~~

~~a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger;~~

~~wherein the heat exchanger is further adapted to retain heat, such that, upon turning off the fluid inlet after dispensing fluid, any fluid remaining in the heat exchanger evaporates through the fluid outlet responsive thereto.~~

24-29. (cancelled)

30. (currently amended) A method of exchanging heat with a fluid, for heating the fluid, in a system which comprises a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, ~~adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein,~~ comprising a heating element, for heating the fluid, a channel, for enabling the fluid to flow thereinto and therefrom, and for enabling the fluid to be stored therein adapted to ~~heat the heat exchanger,~~ and a storing element, for enabling the storing of fluid in the channel, the heating of the fluid stored in the channel to a stored heated fluid temperature, and the maintaining of the fluid in the channel at the stored heated fluid temperature, and

for enabling the fluid to be substantially rapidly heated by the heating element to a fluid dispensing temperature above the stored heated fluid temperature for dispensing of the fluid ~~adapted to be heated by the heating element, and further adapted to maintain the fluid at a heated fluid temperature, and to enable the fluid element to be heated above the heated fluid temperature substantially rapidly to a fluid dispensing temperature, a fluid inlet, for enabling the fluid to flow into the heat exchanger, and a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger, wherein the method comprises:~~

heating the fluid in the channel, by the heating element; and

heating and maintaining the heating of the fluid stored in the channel at the stored heated fluid temperature, by the storing element, for enabling the fluid to be substantially rapidly heated by the heating element to the fluid dispensing temperature above the stored heated fluid temperature for dispensing of the fluid;

~~enabling fluid to flow through the fluid inlet into the heat exchanger;~~

~~exchanging heat with the fluid in the heat exchanger so as to heat the fluid and store heat energy;~~

~~enabling heated fluid to flow out of the heat exchanger and through the fluid outlet; and~~

~~storing fluid heated to the heated fluid temperature in the storing element so as to retain heat for a substantial period of time to maintain the fluid at the heated fluid temperature.~~

31. (cancelled)

32. (currently amended) The method of claim 30, wherein the heat exchanger is comprised of aluminum, and wherein exchanging heat comprises exchanging heat with the fluid in the aluminum heat exchanger ~~exchanging means~~.

33. (original) The method of claim 30, further comprising a sealing element for sealing the heat exchanger, further comprising sealing the heat exchanger.

34. (currently amended) The method of claim 30, ~~wherein the~~ further comprising a fluid inlet ~~comprises an inlet valve~~, and further comprising a ~~wherein~~ enabling fluid inlet flow which comprises enabling the fluid to flow through the fluid inlet ~~inlet valve~~.

35. (currently amended) The method of claim 30, ~~wherein the~~ further comprising a fluid outlet ~~flow comprises an outlet valve~~, and further comprising a ~~wherein enabling~~ fluid outlet flow which comprises enabling the fluid to flow through the fluid outlet ~~outlet valve~~.

36. (original) The method of claim 30, further comprising a sensing element for sensing the temperature of the heat exchanger and for controlling and stabilizing the temperature thereof, further comprising sensing the temperature of the heat exchanger and controlling and stabilizing the temperature thereof.



37. (original) The method of claim 30, further comprising a system for dispensing the fluid, which includes the heat exchanger therein, further comprising dispensing the fluid from the fluid dispensing system.

38. (currently amended) The method of claim 30, further comprising a fluid inlet, for enabling the fluid to flow into the channel, and wherein the storing element is further adapted to retain heat, such that, upon turning off the heating element and the fluid inlet after dispensing fluid, any fluid remaining in the channel heat-exchanger evaporates through the fluid outlet responsive thereto, further comprising evaporating any fluid remaining in the channel heat-exchanger, after dispensing fluid, responsive to the retained heat in the storing element.

39. (currently amended) The method of claim 30, further comprising a fluid outlet, for enabling the fluid to flow out of the channel, and a flow-controlling element for controlling the flow of the fluid from the fluid outlet for dispensing thereof, and further comprising controlling the flow of the fluid from the fluid outlet for dispensing thereof.

40. (original) The method of claim 30, further comprising an operation-controlling element for controlling the operation of the system, further comprising controlling the operation of the system.

41. (currently amended) The method of claim 30 ~~31~~, wherein the storing element is adapted to enable the fluid to be in direct contact therewith, and wherein exchanging heat comprises enabling fluid to be in direct contact with the storing element.

42. (cancelled)

43. (currently amended) The method of claim 30 ~~31~~, wherein the heating element is generally m-shaped, and wherein exchanging heat further comprises heating the storing element through the generally m-shaped heating element.

44. (currently amended) The method of claim 30 ~~31~~, wherein the heating element is adapted to be connected to a power source, and wherein exchanging heat further comprises heating the heating element upon actuating the power source.

45. (currently amended) The method of claim 30 ~~31~~, wherein the channel is in the shape of a spiral ~~generally spiral-shaped~~, and wherein exchanging heat further comprises enabling fluid to flow into the ~~generally~~ spiral-shaped channel.

46. (original) The method of claim 37, wherein the heat exchanger is located generally in the upper portion of the fluid dispensing system, and wherein exchanging heat further comprises exchanging heat in the generally upper portion of the fluid dispensing system.

47. (original) The method of claim 37, wherein the fluid dispensing system further includes an outlet for dispensing the heated fluid, and wherein dispensing further comprises dispensing the fluid from the heated fluid dispensing outlet.

48. (original) The method of claim 39, wherein the flow-controlling element comprises a flowmeter, and wherein controlling further comprises controlling the flow of the fluid in the flowmeter.

49. (original) The method of claim 40, wherein the operation-controlling element comprises a processing element for processing the temperature of the heat exchanger, and wherein operation-controlling further comprises processing the temperature of the heat exchanger.

50. (original) The method of claim 46, wherein the fluid dispensing outlet comprises a fluid spray head, and wherein dispensing further comprises dispensing through the fluid spray head.

51. (original) The method of claim 49, wherein the processing element comprises a microprocessor, and wherein sensing further comprises processing through a microprocessor.

52. (currently amended) A method of exchanging heat with a fluid, for heating the fluid, in a system which comprises heat exchanging means ~~a heat exchanger~~, for exchanging heat with a fluid so as to heat the fluid, comprising heating means, for

heating the fluid, a channel, for enabling the fluid to flow thereinto and therefrom, and for enabling the fluid to be stored therein, and storing means, for enabling the storing of fluid in the channel, the heating of the fluid stored in the channel at a stored heated fluid temperature, and the maintaining of the fluid in the channel at the stored heated fluid temperature, and for enabling the fluid to be substantially rapidly heated by the heating means to a fluid dispensing temperature above the stored heated fluid temperature for dispensing of the fluid, ~~adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, a fluid inlet, for enabling the fluid to flow into the heat exchanger, and a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger, wherein the heat exchanger is further adapted to retain heat, such that, upon turning off the fluid inlet, after dispensing fluid, any fluid remaining in the heat exchanger evaporates through the fluid outlet responsive thereto, and,~~ wherein the method comprises:

heating the fluid in the channel, by the heating means; and

heating and maintaining the heating of the fluid stored in the channel at the stored heated fluid temperature, by the storing means, for enabling the fluid to be substantially rapidly heated by the heating means to the fluid dispensing temperature above the stored heated fluid temperature for dispensing of the fluid.

~~enabling fluid to flow through the fluid inlet into the heat exchanger;~~

~~exchanging heat with the fluid in the heat exchanger so as to heat the fluid and store heat energy;~~

~~enabling heated fluid to flow out of the heat exchanger and through the fluid outlet;~~

~~turning off the fluid inlet;~~

~~dispensing fluid; and~~

~~evaporating any fluid remaining in the heat exchanger through the fluid outlet, responsive to the retained heat in the heat exchanger.~~

53-58. (cancelled)

59. (previously presented) The system of claim 4, wherein the sealing element comprises a pair of plates, in which each plate is relatively thin, and the storing element is located between the pair of sealing element plates, and comprises a storing element plate which is relatively thick, wherein the thickness of the storing element plate is substantially greater than the thickness of each relatively thin sealing element plate, such that the storing element plate is adapted to retain heat for a substantial period of time to maintain the fluid at the heated fluid temperature.

60. (previously presented) The method of claim 33, wherein the sealing element comprises a pair of plates, in which each plate is relatively thin, and the storing element is located between the pair of sealing element plates, and comprises a storing element plate which is relatively thick, wherein the thickness of the storing element plate is substantially greater than the thickness of each relatively thin sealing element plate, such that the storing element plate is adapted to retain heat for a substantial period of time to maintain the fluid at the heated fluid temperature, and wherein storing further comprises storing fluid heated to the heated fluid temperature in the relatively thick storing element plate so as to retain heat for a substantial period of time to maintain the fluid at the heated fluid temperature.

61-61. (cancelled)